

10W40 SN/CF-4

DEFINITION

10W40 SN is a premium, multi grade petrol/diesel oil that provides maximum protection in all climates with long life capabilities. **10W40 SN** has been formulated with the latest additive technology and choice of base stocks to meet these criteria and give the required protection to all vital engine and engine/transmission components.

10W40 SN will reduce oil consumption and has excellent circulation capabilities due to its high viscosity index enabling it to protect the engine during cold temperature start up.

10W40 SN meets or exceeds the following specifications.

- * API SN/CF ILSAC GF-4
- * JASO VTW
- * CCMC G4, D4, PD-2
- * DAIMLER BENZ DB 229.1
- * VW 501.01 and 505.00
- * FORD ESE-M2C153E
- * ACEA A3, B3

APPLICATIONS

10W40 SN motor oil is suitable for all late model petrol engine vehicles including those fitted with turbo chargers. Ideal for use in L.P.G. fuelled vehicles and lightly loaded diesel engines.

10W40 SN meets or exceeds the requirements of an SN/CF engine oil. It provides high performance wear control, wide temperature range fluidity with minimal sludge deposits.

PACKAGE SIZE

Bulk, 205 Litre, 60 Litre, 20 Litre.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	10W40 SN/CF- 4
Specific gravity at 15c	0.878
Kinematic viscosity at 40 C, mm ² /s (cSt)	96
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.5
Viscosity index	150
Phosphorous maximum %	0.90
TBN, mgKOH/g	9.0

Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.
All Packages should be stored under cover to avoid water contamination and fading. Products should not be

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com.au