

# **SUPER GT 20W50 SJ/CF-4**

## **DEFINITION**

(Code: 1001)

**SUPER GT 20W50 SJ** is a wide range petrol/diesel motor oil which maintains thick oil films for added protection in hard working engines and hot climates.

**SUPER GT 20W50 SJ** meets the following specifications.

API SJ/CF4

VW 500/501

Ford ESE-M2C-153E

MIL-L46152E,2104E

## **APPLICATIONS**

**SUPER GT 20W50 SJ** is engineered to exceed the demands of high-performance engines that operate under severe conditions and is suitable for all late model petrol engine vehicles including those fitted with turbo chargers. Also 20W50 SJ may be used in light diesel engines and petrol engines converted to LPG operation.

## **PROPERTIES**

**SUPER GT 20W50 SJ** meets the requirements of an SJ/CF engine oil. It has excellent sludge and varnish control for a cleaner engine.

## **package size**

**Bulk, 205 Litre, 60 Litre, 20 Litre**

## **typical main characteristics**

<b>CHARACTERISTICS</b>	<b>SUPER GT 20W50 SJ/CF-4</b>
Specific gravity at 15 C	0.889
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	180
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	19.0
Viscosity index	120
TBN, mgKOH/g	7.1
Pour Point	-16

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

### **AUSFIELD LUBRICANTS**

36 Mickle St, Dandenong South VIC 3175 PHONE: (03) 9768 3532 FAX: (03) 9768 3534 EMAIL:  
ausfieldlubricants@bigpond.com