

S.G.T. 20W50 SL/CF4

definition

(Code: 1002)

S.G.T. 20W50 SL is a superior multigrade oil designed for today's modern engine. Combining top quality base oils blended with state of the art additive technology, 20W50 SL can in turn offer improved engine protection from piston deposits and exceptional anti-wear protection.

S.G.T. 20W50 SL meets or exceeds the following specifications.

- * API SL, SJ, SG /CF-4
- * US MILITARY ~ MIL-L-46152E, 2104E
- * CCMC G4, D4, PD-2
- * ACEA A2-96, B2-96
- * DAIMLER BENZ DB 226.1
- * FORD ESE-M2C153E

APPLICATIONS

S.G.T. 20W50 SL motor oil is suitable for use in LPG and lightly loaded diesel engines including those fitted with turbo chargers. An excellent oil choice for everyday driving conditions!

PROPERTIES

S.G.T. 20W50 SL meets or exceeds the requirements of an SL/CF4 engine oil. It meets the latest specifications of nearly all modern engine manufacturers and OEM's.

PACKAGE SIZE

20 Litre, 60 Litre, 205 Litre, Bulk.

typical main characteristics

CHARACTERISTICS	S.G.T. 20W50 SL/CF- 4
Specific gravity at 15 C	0.889
Kinematic viscosity at 40 C, mm ² /s (cSt)	160
Kinematic viscosity at 100 C, mm ² /s (cSt)	18.4
Viscosity index	130
Sulfated ash, %	1.15
TBN, mgKOH/g	8.7

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

AUSFIELD LUBRICANTS

36 Mickle St, Dandenong South VIC 3175 PHONE: (03) 9768 3532 FAX: (03) 9768 3534 EMAIL:
ausfieldlubricants@bigpond.com