

20W50 SN/CF4

(Code: 1009)

definition

20W50 SN is the latest multifunctional petrol/diesel oil incorporating the latest additive technology providing a new generation motor oil, with unsurpassed engine protection.

20W50 SN meets or exceeds the following specifications.

API SN, SM, SL, SJ/CF-4
US MILITARY ~ MIL-L-46152E, 21046
CCMC G4, D4, PD-2
DAIMLER BENZ DB 226.1
FORD ESE-M2C153E
VW 500/501/505
BMW "Special Oil"

APPLICATIONS

20W50 SN motor oil is suitable for all late model petrol engine vehicles including those fitted with turbo chargers. Also suitable for use in LPG and lightly loaded diesel engines both naturally aspirated and turbo-charged.

PROPERTIES

20W50 SN meets or exceeds the requirements of an SM/CF4 engine oil and assists in maintaining engine cleanliness in all engines using both leaded and unleaded fuels.

PACKAGE SIZE

20 Litre, 60 Litre, 205 Litre, Bulk.

typical main characteristics

CHARACTERISTICS	20W50 SN/CF- 4
Specific gravity at 15 C	0.889
Kinematic viscosity at 40 C, mm ² /s (cSt)	165
Kinematic viscosity at 100 C, mm ² /s (cSt)	18.8
Viscosity index	135
Phosphorous maximum %	0.90
TBN, mgKOH/g	9.0

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website
www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

AUSFIELD LUBRICANTS

36 Mickle St, Dandenong South VIC 3175 PHONE: (03) 9768 3532 FAX: (03) 9768 3534 EMAIL:
ausfieldlubricants@bigpond.com