

15W40 SM/CF-4

(Code: 1503)

DEFINITION

HIGH TECH 15W40 SM is a multi grade engine oil that provides superior engine protection suitable for today's multi-valve and conventional engines. Incorporating the latest additive technology, designed for today's conditions, It provides optimum protection against sludge formation, higher temperatures and helps keep the engine clean and free of deposits under high speed high stress motoring conditions.

HIGH TECH 15W40 SM provides good wear protection at low temperatures combining easy low temperature engine startup and fast oil circulation at cold start up when the engine is at its most critical.

HIGH TECH 15W40 SM meets or exceeds the following specifications.

- * API SM/CF
- * JASO VTW
- * CCMC G4, D4, PD-2
- * DAIMLER BENZ DB 229.1
- * VW 501.01 and 505.00
- * FORD ESE-M2C153E
- * ACEA A3, B3

APPLICATIONS

HIGH TECH 15W40 SM is formulated for all types of passenger, 4WD, and light commercial vehicle engines covering Petrol, Diesel and LPG naturally aspirated or turbo charged.

HIGH TECH 15W40 SM meets or exceeds the requirements of an SM/CF engine oil. It has an highly effective detergent and dispersant system to keep engine internals clean. It provides a high level of protection against wear and assists in energy conservation and fuel economy.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	15W40 SM/CF- 4
Specific gravity at 15c	0.882
Kinematic viscosity at 40 C, mm ² /s (cSt)	112
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.5
Viscosity index	142
Phosphorous maximum %	0.90
TBN, mgKOH/g	9.1

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www. @ausfieldlubricants.com.au
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.
- All Packages should be stored under cover to avoid water contamination and fading. Do not store products over 60°C

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com