

4 STROKE – SAE: 30

DEFINITION

(Code: 1830)

4 STROKE OIL SAE 30 is designed for small petrol and diesel engines. It is a mono grade SAE 30 oil ideally suited for lawn mowers, brush cutters and small agricultural stationary equipment etc.

4 STROKE OIL SAE 30 meets or exceeds the following specifications:

- API SG/CD
- Briggs & Stratton
- ACEA E2
- GM
- Ford

APPLICATIONS

4 STROKE OIL SAE 30 is the ideal choice of lubricant for small engines that need “running in”

PROPERTIES

4 STROKE OIL SAE 30 meets or exceeds the requirements of an SG/CD engine oil. It provides a high level of protection against wear, sludge formation and acid corrosion during the service period.

PACKAGE SIZE

205 litre, 60 Litre, 20 litre.

TYPICAL MAIN CHARACTERISTICS

| CHARACTERISTICS | 4 STROKE OIL SAE 30 |
|--|---------------------|
| Specific gravity at 15 C | 0.894 |
| Colour | Red |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 95 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 10.5 |
| Viscosity index | 109 |
| TBN, mgKOH/g | 5.8 |
| Sulfated ash, % | 0.85 |

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com