

2-STROKE

DEFINITION

(Code: 1900)

2-STROKE is a low ash high performance two stroke engine oil for suitable for use in all two stroke Japanese and European motorcycle engines.

2-STROKE meets or exceeds the following specifications.

* JASO FB

* API TA/TB/TC

* ISO EGB

APPLICATIONS

2-STROKE is formulated to reduce the build-up of carbon deposits on critical engine parts that can restrict the flow of gases from the engine, resulting in a decrease in power or deposit-induced pre ignition.

2-STROKE should be used in conjunction with the engine manufactures recommendation regarding fuel/oil ratio however, In the absence of such information a 30 to 1 fuel/oil ratio is advised.

2-STROKE is specifically recommended for lubrication of two-stroke engines that require API TC and JASO FB performance levels.

2-STROKE is not recommended for water-cooled two-stroke marine outboards.

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

CHARACTERISTICS 2-STROKE

Colour	Green
Specific gravity at 15 C	0.856
Kinematic viscosity at 40 C, mm ² /s (cSt)	63
Kinematic viscosity at 100 C, mm ² /s (cSt)	9.3
Viscosity index	106
Sulphated Ash	0.28

RECOMMENDED USES

Suitable for all Two stroke engines operating on leaded or unleaded petrol with or without injection lubrication systems:- Motorcycles, Lawnmowers, Brushcutters, Generators, Pumps, Agricultural Machinery, Chainsaws

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C