

# ***SUPER OUTBOARD OIL***

## ***TCW III***

### **DEFINITION**

(Code: 1950)

**SUPER OUTBOARD OIL** is a premium low smoke engine oil combined with an ashless additive system, designed for all water cooled two stroke outboard engines including oil injected and pre mix systems.

**SUPER OUTBOARD OIL** meets or exceeds the following specifications.

- \* API TD
- \* NMMA TCW 3
- \* ISO L-ETD

### **APPLICATIONS**

**SUPER OUTBOARD OIL** is self-mixing and suitable for oil injection systems often fitted to modern two stroke outboards.

**SUPER OUTBOARD OIL** should be mixed according to the ratio recommended by the manufacturer. It can be used at fuel/oil ratios of up to 100/1 however, 50/1 ratio is advised in the absence of engine recommendations.

### **PROPERTIES**

**SUPER OUTBOARD OIL** is approved by the National Manufacturers Association (NMMA) for service TC-W3

**SUPER OUTBOARD OIL** assists in maintaining engine cleanliness in all water cooled two stroke outboard engines or air cooled engines using both leaded and unleaded fuels.

### **PACKAGE SIZE**

**205 Litre, 60 Litre, 20 Litre**

### **CHARACTERISTICS**

### **SUPER OUTBOARD OIL**

Colour	BLUE
Specific gravity at 15 C	0.87
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	48.7
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	7.2
Viscosity index	110

Suitable for all outboard two stroke engines operating on leaded or unleaded petrol with or without injection lubrication systems:- Evinrude, Mercury, Yamaha, Tohatsu, Johnson, Force, Suzuki, Mariner

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

**AUSFIELD LUBRICANTS**  
Factory 1/36 Mickle St, Dandenong  
South VIC 3175  
PHONE: (03) 9768 3532  
FAX: (03) 9768 3534  
EMAIL:  
[ausfieldlubricants@bigpond.com](mailto:ausfieldlubricants@bigpond.com)