

Supertech 15W40 CK-4/SN

definition

(Code: 1984)

15W40 CK4/SN is a Low Saps, new generation, premium heavy duty diesel oil that has been formulated specifically to meet the latest Euro VI requirements of Australian and imported designed low emission engines. Designed and formulated to provide exceptional protection for highly rated diesel engines running in severe service conditions. It affords increased fuel economy, long drain intervals and prolonged engine life.

OEM Approval

15W40 meets or exceeds the following specifications.

- API CK-4, CJ-4, CI-4
- API, SN, SM, SL
- ACEA E7-12, E9-12
- MAN 3275 & 3575
- DQC III-10-LA
- FORD WSS-M2C171-E AND -F1
- Caterpillar ECF-3
- MB 228.31
- MTU 2.1
- JASO DH-2

OEM APPROVED
CUMMINS CES 20086
DETROIT DIESEL DDC93K222
VOLVO VDS4.5
MACK EO-S 4.5
RENAULT IV RLD 3

BENEFITS

OEM APPROVED- CUMMINS, DETROIT DIESEL, VOLVO, MACK, RENAULT

SPECIALLY FORMULATED TO PROTECT AFTER EXHAUST SYSTEMS

EXCELLENT SOOT DISPERSANCY

SUPERIOR FRICTION AND WEAR CONTROL

LONGER DRAIN INTERVALS

package size

1000 Litre, 205 Litre, 60 Litre, 20 Litre.
typical main characteristics

CHARACTERISTICS	15W40 CK- 4/SN
Specific gravity at 15c	0.868
Kinematic viscosity at 40 C, mm ² /s (cSt)	112
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.7
Viscosity index	135