

# XDO 15W40 CH-4/SJ

(Code: 2001)

## definition

**15W40 CH4** is a heavy duty multigrade diesel engine oil designed for use in high speed, four stroke diesel engines meeting the requirements of American, European and Japanese engine manufactures. **15W40 CH4** meets or exceeds the following specifications.

- \* API CH-4/SJ
- \* VOLVO VDS-2
- \* ACEA A3, B3, E2
- \* MTU Type 2
- \* US MILITARY - MIL-L-2104E, MIL-L- 46152E.
- \* GENERAL MOTORS 6048M, 6G49M, 6085M.
- \* MACK EO-M, EO-M PLUS
- \* CUMMINS CES 20076, 20071
- \* FORD ESE-M2C-1 53E, E8N-M2C-1 21 B
- \* ALLISON Type C-4 (SAE 30)
- \* DETROIT DIESEL Series 40, 50, 55, 60 engines

## APPLICATIONS

**15W40 CH4** is designed to meet 1998 emission standards, It has been formulated for heavy duty service in engines specifically designed for on-highway conditions as well as being suitable for a wide range of heavy-duty off-highway applications.

## PACKAGE SIZE

**Bulk, 205 Litre, 60 Litre, 20 Litre.**

## TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	15W40 CH- 4/SJ
Specific gravity at 15c	0.885
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	115
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	14.7
Viscosity index	139
Sulfated ash %	1.2%
TBN, mgKOH/g	8.9

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

### AUSFIELD LUBRICANTS

Factory 1/36 Mickle St, Dandenong South VIC 3175 PHONE: (03) 9768 3532 FAX: (03) 9768 3534 EMAIL:

[ausfieldlubricants@bigpond.com](mailto:ausfieldlubricants@bigpond.com)