

SAE 10, 30, 40

API: CF/SJ

(Code: 2210, 2230, 2240)

DESCRIPTION

SAE oils are mono grade automotive engine oils designed for a wide range of petrol and diesel engines. Primarily recommended for use as a single oil in mixed fleets containing both light and heavy duty, four stroke diesel and petrol engines, both naturally aspirated and turbocharged, where a mono grade oil is recommended They are available in SAE: 10W, 30 and 40 grades.

The Mid phosphorous level and Mid sulphated ash content ensures its use for mixed fleet operators including those with petrol engines with catalytic converters.

SAE oils meets or exceeds the following specifications:

- * API CF/SJ
- * MIL-L-46152E/2104C
- * CCMC G4/D4/PD2
- * DAIMLER BENZ DB 227.1
- *ACEA E2(SAE 30,40)
- *Mercedes Benz 228.0 (SAE 30, 40)
- *Mack EO-K/2
- *Japan Japanese CD

APPLICATIONS

SAE oils are also recommended for generator sets and high speed diesel engines in marine service. Can be used in non engine applications where oils of its performance level are suitable, such as manual and power lift transmissions and mobile hydraulic systems.

PACKAGE SIZE

205 litre, 60 Litre, 20 litre.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	SAE	10W	30W	40W
Specific gravity at 15 C		0.899	0.878	0.901
Kinematic viscosity at 40 C, mm ² /s (cSt)		42	99	140
Kinematic viscosity at 100 C, mm ² /s (cSt)		6.2	10.5	14.5
Viscosity index		95	98	101
Flash Point		210	206	220
Pour Point		-32	-21	-18
Sulfated ash, %		1.05	1.05	1.05

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com.au