

MULTIFARM

STOU 15W40

DEFINITION

(Code: 2600)

MULTIFARM is a multi-purpose lubricant designed to lubricate a wide range of applications on farm. Developed with special frictional additives specifically to deliver protection and performance for engines, transmissions, hydraulics, wet brakes and front axle.

MULTIFARM meets or exceeds the following specifications.

API CF/CE/SG ; CCMC D3/G3
API GL4 LOAD CAPACITY
ALLISON C4
CASE JIC 185 & MS 1206
US MILITARY MIL-L-2104D, 46152D
MACK EOK-2
DAIMLER BENZ DB 227.1
CATERPILLAR TO-2
JOHN DEERE HYGARD/J20C, JD27A
MASSEY FERGUSON MF1139, MF1144
FORD/NEW HOLLAND M2C-1 59A, M2C-1 59B

It is also suitable for all petrol and diesel engines. The low phosphorous level is controlled to meet the requirements of Australian passenger car manufacturers. It has also been formulated for use as a gear lubricant (to API GL-4, SAE 80W-90 performance level).

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	MULTIFARM STOU 15W40
Specific gravity at 15 C	0.889
Kinematic viscosity at 40 C, mm ² /s (cSt)	115
Kinematic viscosity at 100 C, mm ² /s (cSt)	13.8
Viscosity index	115
TBN, mgKOH/g	10
Sulfated ash, %	1.4

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com