

ATF DEX II-D

(Code: 3001)

DEFINITION

ATF DEXRON II-D is an oil with a high viscosity index formulated to meet Dexron II and Ford specifications.

ATF DEXRON II-D has excellent shear stability for long fluid life,

ATF DEXRON II-D meets or exceeds the following specifications.

GENERAL MOTORS - DEXRON II D
FORD - M2C138 - CJ, M2C166H, MERCON, BTR - 5M-52
ALLISON - C3
CATERPILLAR - TO-2
SPERRY VICKERS - HYDRAULIC PUMP SYSTEMS
DENISON - HYDRAULIC PUMP SYSTEMS
SUNSTRAND - HYDRAULIC PUMP SYSTEMS
DAIMLER BENZ DB 226.1

APPLICATIONS

ATF DEXRON II-D is also commonly used as a power steering fluid. This product is also approved for use where Allison C3 fluid is recommended.

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	ATF-DEXRON II-D
Kinematic viscosity at 40 C, mm ² /s (cSt)	43
Kinematic viscosity at 100 C, mm ² /s (cSt)	8.5
Pour point deg C	-40
Viscosity index	161
Colour	RED

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com