

ATF DEX III (3)

(Code: 3100)

DEFINITION

DEXRON III is transmission fluid designed for use in automatic transmissions where Dexron® III or Dexron® II fluids have been specified. This product is a high viscosity index fluid containing superior additive technology and greatly improved low temperature properties for smooth cold shifts.

DEXRON III meets or exceeds the following specifications.

GENERAL MOTORS - DEXRON III
FORD MERCON
ALLISON C-4
CATERPILLAR TO-2
SPERRY VICKERS - HYDRAULIC PUMP SYSTEMS
DENISON - HYDRAULIC PUMP SYSTEMS
SUNSTRAND - HYDRAULIC PUMP SYSTEMS

APPLICATIONS

DEXRON III is also commonly used as a power steering fluid. This product is also approved for use where Allison C-4 fluid is recommended.

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	DEXRON III
Kinematic viscosity at 40 C, mm ² /s (cSt)	38
Kinematic viscosity at 100 C, mm ² /s (cSt)	7.4
Pour point deg C	-42
Viscosity index	160
Colour	RED

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com