

GEAR LUBE

80W90 & 85W140 GL-5

(Code: 4004, 4007)

DEFINITION

GEAR LUBES is a multigrade lubricant offering superior wear protection and excellent low temperature characteristics designed to give maximum protection to gearboxes and differentials.

GEAR LUBES is ideal for modern 4 and 5 speed manual gearboxes and is designed to give maximum protection to gearboxes and differentials operating in severe conditions.

GEAR LUBES meet or exceed the following specifications.

- * API - GL5
- * MILITARY SPECIFICATIONS MIL - L - 2105D
- * GENERAL MOTORS HN-1181, HN-1187, HN -1386.
- * FORD - M2C108 - A, M2C105 - A
- * MACK GO - H
- * BORG WARNER 5M - 26
- * DAIMLER - BENZ 235/2F
- * ROCKWELL STANDARD 0 - 76D, 0 - 76A

APPLICATIONS

GEAR LUBES are engineered for performance in heavy-duty commercial transmissions, axles, and final drives where extreme pressures and shock loading are expected

CHARACTERISTICS

	<u>80W90</u>	<u>85W140</u>
Viscosity Index	115	120
Viscosity @ 100 C (Cst)	17.0	28
Viscosity @ 40 C (Cst)	175	362

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com