

LIMITED SLIP

GEAR OIL LS90

(Code: 4006)

DEFINITION

LS GEAR OIL 90 Is an extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid axles, both with and without "limited slip" design. It contains extreme pressure additives and special friction modifiers.

LS GEAR OIL 90 meets or exceed the following specifications.

- * MILITARY SPECIFICATIONS MIL-PRF-2105E
- * GENERAL MOTORS - HN.1386, HN. 1561, HN. 1187.
- * FORD-M2C104-A, M2C105-A,M2C119-A,
- * M2C1006-A, M2C1006B.
- * BORG WARNER - 5M - 31
- * API GL-5

APPLICATIONS

LS GEAR OIL 90 Should be used in all limited slip differentials including Ford "Traction - Lok" type.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	Limited Slip LS90
Specific gravity at 15 C	0.901
Kinematic viscosity at 40 C, mm ² /s (cSt)	200
Kinematic viscosity at 100 C, mm ² /s (cSt)	17.7
Viscosity index	107
Flash Point C	210

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com