

LIMITED SLIP GEAR OIL LS140

(Code: 4009)

DEFINITION

LS GEAR OIL 140 is an extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid axles, both with and without "limited slip" design. It contains extreme pressure additives and special friction modifiers.

LS GEAR OIL 140 meets or exceeds the following specifications.

- * MILITARY SPECIFICATIONS MIL-PRF-2105E
- * GENERAL MOTORS - HN.1386, HN. 1561, HN. 1187.
- * FORD-M2C104-A, M2C105-A, M2C119-A,
- * M2C1006-A, M2C1006B.
- * BORG WARNER - 5M - 31
- * API GL-5

APPLICATIONS

LS GEAR OIL 140 Should be used in all limited slip differentials including Ford "Traction - Lok" type.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	Limited Slip LS140
Specific gravity at 15 C	0.911
Kinematic viscosity at 40 C, mm ² /s (cSt)	330
Kinematic viscosity at 100 C, mm ² /s (cSt)	30
Viscosity index	110
Flash Point C	208

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS

Factory 1/36 Mickle St, Dandenong South VIC 3175 PHONE: (03) 9768 3532 FAX: (03) 9768 3534 EMAIL: ausfieldlubricants@bigpond.com