

ROAD RANGER 50

(Code: 4010)

DEFINITION

ROAD RANGER is a purpose lubricant designed for the trucking industry where manual gearboxes such as Road Ranger, Eaton Fuller, Rockwell and Spicer are commonly fitted.

APPLICATIONS

ROAD RANGER gives excellent protection to gearboxes operating under conditions where high heat and heavy loads.

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	Road Ranger 50
Specific gravity at 15 C	0.889
Kinematic viscosity at 40 C, mm ² /s (cSt)	220
Kinematic viscosity at 100 C, mm ² /s (cSt)	16.9
Viscosity index	120
Flash Point C	216
Grade (Gear Class)	SAE 90
Grade (Engine Class)	SAE 50

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com