

RX80 ***75W80 GL-5***

DEFINITION

RX80 75W80 is a multigrade lubricant offering superior wear protection and excellent low temperature characteristics designed to give maximum protection to gearboxes and differentials.

RX80 75W80 is ideal for modern 4 and 5 speed manual gearboxes and is designed to give maximum protection to gearboxes and differentials operating in severe conditions.

RX80 75W80 meet or exceed the following specifications.

- * API - GL5
- * FORD ESP-M2C83-C
- * BORG WARNER 5M-42
- * MITSUBISHI ES-X-64021
- * MIL-L-2105D

APPLICATIONS

RX80 75W80 is engineered for performance in heavy-duty commercial transmissions, axles, and final drives where extreme pressures and shock loading are expected.

CHARACTERISTICS

| | <u>75W80</u> |
|-------------------------|---------------------|
| Viscosity Index | 150 |
| Viscosity @ 100 C (Cst) | 14.0 |
| Viscosity @ 40 C (Cst) | 110 |

Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS

36 Mickle St, Dandenong South VIC 3175 PHONE: (03) 9768 3532 FAX: (03) 9768 3534 EMAIL: ausfieldlubricants@bigpond.com