

COMPRESSOR OIL

ISO: 32,46,68,100,150

(Code: 7010, 7011, 7012, 7013, 7014)

COMPRESSOR OIL is a range of Air compressor lubricants formulated from highly refined base oils and “state of the art” non-hydrolyzing anti wear additives developed for rotary screw and reciprocating air compressors. The result is a finished product which has long life, protects compressor components from wear and also separates readily from water.

PROPERTIES

ISO Grade:	32,	46,	68,	100,	150,
Viscosity at 40 C, (cSt)	30	44	64	95	143
Viscosity at 100 C,(cSt)	5.3	6.7	8.5	10.8	14.0
Flash point C	180	199	205	210	220
Pour point C	-18	-18	-18	-9	-9
Density	0.87	0.87	0.87	0.8	0.89
Viscosity Index	95	95	95	95	95
Thermo-oxidative Stability C.C. Residue %	0.79	0.80	0.84	0.90	0.96

APPLICATIONS

COMPRESSOR OIL Grades result in longer valve cleaning intervals as a result of high resistance to deposit formation and outstanding oxidation stability. They are designed for use up to 2000 hours with air discharge temperatures of up to 85°C.

Drain intervals can be extended to up to 4000 hours in rotary screw compressors where an oil test program is in place.

PACKAGE SIZE

205 Litre, 60, Litre, 20 Litre

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com