

# **INDUSTRIAL GEAR OIL**

## **ISO: 68, 100, 150, 220, 320, 460**

(Code: 7020, 7021, 7022, 7023, 7024, 7025)

### **DEFINITION**

**INDUSTRIAL GEAR OILS** are premium quality industrial gear lubricants manufactured from highly refined base stocks and lead- free Extreme Pressure agents.

**INDUSTRIAL GEAR OILS** meet or exceed the following specifications,

API GL-3  
AGMA 250.04, 9005-D94  
U.S STEEL 224  
DAVID BROWN S1.53.101(E)  
DIN 51 517 (PART 3)

### **FEATURES**

- > Protects against rust and corrosion
- > Excellent Demulsibility.
- > Particularly suited for steel on bronze industrial worm gears.
- > Good oxidation and thermal stability for long life.

### **APPLICATIONS**

**INDUSTRIAL GEAR OILS** may be used in all types of industrial gear boxes and can also be used in sprockets, chain drives and slide guides.

### **CHARACTERISTICS**

**INDUSTRIAL GEAR OILS** are available in the following grades.

<b>PRODUCT</b>	<b>ISO GRADE</b>	<b>Viscosity @ 40 C</b>	<b>Viscosity @ 100 C</b>
Industrial Gear Oil	68	62	8.7
Industrial Gear Oil	100	96	14.0
Industrial Gear Oil	150	142	18.0
Industrial Gear Oil	220	212	23.0
Industrial Gear Oil	320	312	25.0
Industrial Gear Oil	460	440	31.0

### **PACKAGE SIZE**

**205 Litre, 60 Litre, 20 Litre.**

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

**AUSFIELD LUBRICANTS**  
Factory 1/36 Mickle St, Dandenong  
South VIC 3175  
PHONE: (03) 9768 3532  
FAX: (03) 9768 3534  
EMAIL:  
[ausfieldlubricants@bigpond.com](mailto:ausfieldlubricants@bigpond.com)