

# **CHAIN & BAR OIL**

## **ISO 150,220,320**

### **DEFINITION**

(Code: 7031, 7032, 7033)

**CHAINBAR OIL** is a tacky oil, designed to protect saw teeth and chains from abrasive wear.

**CHAINBAR OIL** is an extreme pressure pressure lubricant developed with additives that reduce throw off and improve performance.

### **PROPERTIES**

|                       |            |            |            |
|-----------------------|------------|------------|------------|
| Grade ISO             | <b>320</b> | <b>220</b> | <b>150</b> |
| Viscosity @ 40 C cSt  | 310        | 212        | 146        |
| Viscosity @ 100 C cst | 26.0       | 18.3       | 13.9       |
| Pour Point deg C      | -12        | -13        | -14        |

### **PACKAGE SIZE**

**205 Litre, 60 Litre, 20 Litre.**

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

**AUSFIELDLUBRICANTS**  
Factory 1/36 Mickle St, Dandenong  
South VIC 3175  
PHONE: (03) 9768 3532  
FAX: (03) 9768 3534  
EMAIL:  
[ausfieldlubricants@bigpond.com](mailto:ausfieldlubricants@bigpond.com)