

# ROCKDRILL OIL

## 100, 150, 220, 320

(Code: 7034, 7035, 7036, 7037)

### DEFINITION

**ROCKDRILL OIL** protects saw teeth and chains from abrasive wear and can be applied manually or in automatic lubrication systems. It is suitable for drilling rig tool bits working in soft or hard rock conditions and will adhere to the working surfaces of pneumatic rams and air motors operating under high speed assisting in increasing equipment life.

**ROCKDRILL** is a tacky extreme pressure and anti-corrosion lubricant with excellent cling characteristics that resists throw off, water wash off and corrosion from tree sap.

### PROPERTIES

Grade ISO	320	220	150	100
Viscosity @ 40 C cSt	310	212	145	106
Viscosity @ 100 C cst	26.0	18.3	13.9	11.3
Pour Point deg C	-12	-13	-14	-18

### APPLICATIONS

**ROCKDRILL OIL** will adhere to the working surfaces of cutter bars, chains, scissor snickers under high speed assisting in increasing equipment life.

**ROCKDRILL OIL** is suitable for all types of machinery where loss of fluid would be undesirable to the surrounding environment including mining equipment, tunnel boring machines, timber mills, steel mills, die-casting plants, drilling rigs etc.

### PACKAGE SIZE

**205 Litre, 60 Litre, 20 Litre.**

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

**AUSFIELD LUBRICANTS**  
Factory 1/36 Mickle St, Dandenong  
South VIC 3175  
PHONE: (03) 9768 3532  
FAX: (03) 9768 3534  
EMAIL:  
[ausfieldlubricants@bigpond.com](mailto:ausfieldlubricants@bigpond.com)