

# ***CONCRETE MOULD OIL***

## **DEFINITION**

(Code: 7063)

**CONCRETE MOULD RELEASE OIL** is a fluid heavily fortified to enable excellent surface conditioning characteristics on porous and non – porous moulds to enable quick release of the mould and impart an excellent surface finish.

## **PROPERTIES**

Grade ISO	20.5
Viscosity @ 40 C cSt	20.0-23.5
Viscosity @ 100 C cst	N/A
Flash Point C	207
Pour Point C	-10

## **APPLICATIONS**

**CONCRETE MOULD RELEASE OIL** is designed for many types of moulds and formwork where concrete, plaster, tile or paver products are being manufactured.

## **PACKAGE SIZE**

**205 Litre, 60 Litre, 20 Litre.**

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

**AUSFIELD LUBRICANTS**  
Factory 1/36 Mickle St, Dandenong  
South VIC 3175  
PHONE: (03) 9768 3532  
FAX: (03) 9768 3534  
EMAIL:  
[ausfieldlubricants@bigpond.com](mailto:ausfieldlubricants@bigpond.com)