

NEAT CUTTING OIL

(Code: 7120)

DEFINITION

CUTTING OIL NEAT is an extreme pressure mineral non-soluble cutting oil with low odour characteristics for machine operators comfort. It contains an extreme pressure additive system, rust and anti-foam additives for long tool life, good heat transfer and surface finish.

PROPERTIES

Grade ISO	22
Viscosity @ 40 C cSt	24
Viscosity @ 100 C cst	4.8
Colour	Dark Amber

APPLICATIONS

CUTTING OIL NEAT is designed for heavy duty machining such as deep hole drilling, tapping, broaching and threading of high carbon alloy and stainless steels.

CUTTING OIL NEAT may stain non-ferrous metals.

CUTTING OIL NEAT does not contain active phosphorous or chlorine extreme pressure materials.

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com.au