

SYN TECH

5W50 SM/CF4, 5W40 SM/CF4

DEFINITION

(Code: 9151 & 9160)

SYN TECH 5W50, 5W40 are fully synthetic petrol/diesel motor oils formulated with advanced synthetic base stocks, premium additives and a broad viscosity rating, providing the highest level of protection in the most demanding of conditions and allowing for maximum drain intervals.

SYN TECH 5W50, 5W40 provides protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

SYN TECH 5W50, 5W40 is a multi viscosity, low pour point motor oil ensuring quick lubrication to all moving parts during cold weather starts.

APPLICATIONS

SYN TECH 5W50, 5W40 meets or exceeds the following specifications.

- * API SM/CF-4
- * ACEA A3/B4
- * JASO VTW
- * CCMC G5, D4, PD-2
- * DAIMLER BENZ DB 229.1, 229.3
- * VW 500.00-505.00
- * PORSCHE and BMW
- * ILSAC GF4

PROPERTIES

SYN TECH 5W50, 5W40 10W40 meets or exceeds the requirements of an SM/CF engine oil and is suitable for unleaded or leaded fuelled engines, diesel powered cars, turbo charged and naturally aspirated engines and LPG engines.

SYN TECH 5W50, 5W40 maintains outstanding engine cleanliness.

PACKAGE SIZE

Bulk, 205 Litre, 60 Litre, 20 Litre.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	SYNTHETIC 5W50	SYNTHETIC 5W40
Specific gravity at 15 C	0.865	0.864
Kinematic viscosity at 40 C, mm ² /s (cSt)	120	89
Kinematic viscosity at 100 C, mm ² /s (cSt)	18.9	15.8
Pour Point deg C	- 32	-36
Viscosity index	190	189
Phosphorous maximum %	0.095	0.095
TBN, mgKOH/g	8.8	8.7

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com