

# SYN

## 5W50 SN/CF4, 5W40 SN/CF4

### DEFINITION

**SYN 5W50, 5W40** are fully synthetic petrol/diesel motor oils formulated with advanced synthetic base stocks, premium additives and a broad viscosity rating, providing the highest level of protection in the most demanding of conditions and allowing for maximum drain intervals.

**SYN 5W50, 5W40** provides protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

**SYN 5W50, 5W40** is a multi viscosity, low pour point motor oil ensuring quick lubrication to all moving parts during cold weather starts.

### APPLICATIONS

**SYN 5W50, 5W40** meets or exceeds the following specifications.

- \* API SN/CF-4
- \* ACEA A3/B4
- \* JASO VTW
- \* CCMC G5, D4, PD-2
- \* DAIMLER BENZ DB 229.1, 229.3
- \* VW 500.00-505.00
- \* PORSCHE and BMW
- \* ILSAC GF4

### PROPERTIES

**SYN 5W50, 5W40** meets or exceeds the requirements of an SN/CF engine oil and is suitable for unleaded or leaded fuelled engines, diesel powered cars, turbo charged and naturally aspirated engines and LPG engines.

**SYN 5W50, 5W40** maintains outstanding engine cleanliness.

### PACKAGE SIZE

**Bulk, 205 Litre, 60 Litre, 20 Litre.**

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	SYNTHETIC 5W50	SYNTHETIC 5W40
Specific gravity at 15 C	0.865	0.864
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	120	89
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	18.9	15.8
Pour Point deg C	- 32	-36
Viscosity index	190	189
Phosphorous maximum %	0.095	0.095
TBN, mgKOH/g	8.8	8.7

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

**AUSFIELD LUBRICANTS**  
Factory 1/36 Mickle St, Dandenong  
South VIC 3175  
PHONE: (03) 9768 3532  
FAX: (03) 9768 3534  
EMAIL:  
[ausfieldlubricants@bigpond.com.au](mailto:ausfieldlubricants@bigpond.com.au)