

Euro Syn E4-E6 Long Drain 10W-40

Fully Synthetic, Low Saps, Ultra High Performance oil.

(Code: 9233)

DEFINITION

EURO - SYN E4-E6 Long Drain is a fully synthetic ultra high performance heavy duty diesel engine oil. It meets and complies with the demanding requirements requirements of Euro 4 exhaust emission legislation.

EURO - SYN E4-E6 Long Drain is ideally designed for European engines requiring SHPD level of performance and those which comply with Euro 1, Euro 2, Euro 3 and Euro 4 Exhaust emission legislation.

EURO - SYN E4-E6 Long Drain is not suitable for American diesels calling for CG-4, CH-4 and CI-4 performance levels. **EURO - SYN E4-E6 Long Drain** meets or exceeds the following specifications.

ACEA E4-08 (2008)

ACEA E6-08 (2008)

API CF MAN 3277

RENAULT TRUCK RLD/RLD-2 MB 228.51 MTU Type 3 RENAULT TRUCK RXD VOLVO VDS 2, VDS 3 DEUTZ DQC IV-05, III-05

SUMMARY OF BENIFITS

- **Full Synthetic Formulation**
- **Suitable for use where particulate filters are used**
- **Super extended drain intervals surpassing any mineral or American diesel type lubricant.**
- **Excellent soot and sludge control resulting in cleaner engines**
- **Reduces fuel consumption due to superior technology.**
- **Outstanding low temperature viscometrics for reduced wear at start up.**
- **Low SAPS (Sulfated Ash, Phosphorous and Sulfur)**

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

CHARACTERISTICS	EURO-SYN E4-E6 Long Drain 10W40
Specific gravity at 15 C	0.890
Flash point, COC C	210
Pour point C	-34
Kinematic viscosity at 100 C, mm ² /s (cSt)	15.2
Kinematic viscosity at 40 C, mm ² /s (cSt)	91
TBN, ASTM D2896, mg KOH/g	19
Viscosity index	180
Sulphated ash, %	1.05

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

AUSFIELD LUBRICANTS

Factory 1/36 Mickle St, Dandenong South VIC 3175 PHONE: (03) 9768 3532 FAX: (03) 9768 3534 EMAIL:

ausfieldlubricants@bigpond.com