

# SYN MULTI-TRANS DX6

## DEFINITION

**SYN MULTI-TRANS** is a new generation multipurpose, full synthetic Automatic Transmission Fluid developed to cover virtually all ATF specifications. With the exception of CVT transmissions and Ford "Type F" transmissions, **Syn Multi-Trans** is truly a one stop Automatic Transmission Fluid. Designed to meet Japanese, American and European transmissions, **Syn Multi-Trans** is the perfect choice for the consumer who does not want to carry multiple drums of product.

**SYN MULTI-TRANS** is an exceptional quality ATF fluid designed to meet the next generation fuel efficient-long life specification fluids. This product is a high viscosity index fluid containing superior additive technology, which provides outstanding service life span, shift pattern performance, clutch life, thermal stability as well as oxidation resistance and sludge control.

**SYN MULTI-TRANS** meets or exceeds the following specifications.

TOYOTA TYPE T, TII, TIII, T IV & D2	SUZUKI ATF OIL, ATF OIL SPECIAL
MAZDA ATF D III, ATF M III	GENERAL MOTORS DEXRON III, VI
NISSAN MATIC FLUID D, FLUID J	FORD MERCON V
MITSUBISHI DIA QUEEN ATF SP II, SP III	ALLISON C4, TES 295, 389
HYUNDAI SP III	CATERPILLAR TO-2
SUBARU ATF	CHRYSLER MS 7176E, MS 9602
DAIHATSU ALUMIX ATF MULTI	DAIMLER BENZ DB 236.6
HONDA Z1	VOITH DIWA 502-2, 502-3, D851 & G607
ISUZU BESCO ATF II, ATF III	ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C
VW TL 521 62	VOLVO 97340
AUDI	FORD NGF
BMW LA2634	MB 236.1 / 236.2 / 236.5 / 236.6 / 236.7 / 236.9
BMW/Esso 71141	

**SYN MULTI-TRANS** is a very versatile fluid and can be used in almost all Japanese and many European and American vehicles as a service fill, and may also be used as a power steering fluid and in hydraulic systems particularly where high temperatures are encountered.

## PACKAGE SIZE

**205 Litre, 60 Litre, 20 Litre.**

## TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	ATF SYN MULTI-TRANS
Density	0.846
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	30.3
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	5.98
Brookfield viscosity at -40 C cP	11,977
Pour point deg C	-43
Viscosity index	191
Colour	AMBER/NATURAL

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website [www.ausfieldlubricants.com.au](http://www.ausfieldlubricants.com.au)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

**AUSFIELD LUBRICANTS**  
36 Mickle St, Dandenong South VIC  
3175 PHONE: (03) 9768 3532 FAX:  
(03) 9768 3534 EMAIL:  
[ausfieldlubricants@bigpond.com](mailto:ausfieldlubricants@bigpond.com)