DETROIT DIESEL

DD 40

(Code: 2200)

DEFINITION

DETROIT DIESEL 40 is a high quality mono - grade diesel SAE 40 engine oil designed to meet the minimum requirements of most diesel engines.

DETROIT DIESEL 40 meets or exceeds the following specifications.

- * API CF-2 / SH
- * SAE 40
- * ACEA E1
- * US MILITARY MIL-L-46152C, 2104D.
- * GENERAL MOTORS DETROIT DIESEL
- * BULLETIN 7SE270 (Revised 9185)

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	DETROIT DIESEL 40	
Specific gravity at 15 C	0.886	
Kinematic viscosity at 100 C, mm2/s (cSt)	14.0	
Viscosity index	105	
Zinc (%wt)	0.11	
TBN, mgKOH/g	6.0	
Sulfated ash, %	0.95	

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated
 are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS

Factory 1/36 Mickle St, Dandenong South VIC 3175 PHONE: (03) 9768 3532 FAX: (03) 9768 3534

EMAIL:

ausfieldlubricants@bigpond.com.au